



Door thickness 40 ~ 50 mm

**FITS THE
EXISTING
DOORS**



Power supply 4 alkaline
batteries



Spindle size 65 mm



Voltage
DC 4,2 V \pm 0,2 V



Operation temperature
-10 °C ~ 55 °C.



Humidity
20% ~ 93% \pm 2RH

* The 36-month warranty period is guaranteed in case of lock assembly made by abiLine company or its authorised distributor. If electronic locks are installed by a client or third party, the product has 24-month warranty.

Be-Tech Smart electronic lock



Be Tech Smart electronic hotel locks are the combination of the newest technology and aesthetic design which fits each interior.



Technical data:

- » Contactless technology standard Mifare 13,56 MHz.
- » EI 30 certificate (compliance with the standard UNE EN 1634 1:2000) confirms fire resistance
- » Designed according to the newest technology
- » Stainless steel handles are solid and easy to use
- » Stainless steel bolt is resistant to impact
- » Mortise lock, 16.2 mm thick, can fit even slim doors
- » Service life of lock body: 1 000 000 times for use
- » Mechanical opening is possible in case of emergency
- » Memory of last 500 events which can be printed
- » Hidden key override
- » Separate card reader and PCB part ensure better protection from unauthorised access
- » Electronic lock elements are resistant to humidity so they can be installed in all rooms including e.g. sauna
- » Sound and light signal about low battery
- » EPROM memory retains its data even when its power supply is off or a lock is repaired
- » POS, PMS: the system can be integrated with all the main systems for hotel management, such as Micros Fidelio Suites or Micros Opera.

more information:

www.betechLocks.com